



Representative image only.
Some models may vary in appearance.



Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Air pressure tested at 500 psi, leak tested with helium, then sealed and nitrogen pressurized.
- Left- or right-hand refrigerant and plumbing connections.
- Externally mounted flowrator body with Schrader valve for hiss-testing.
- Heavy duty plastic or metal drain pans powder coated galvanized steel horizontal drain pans standard.
- Embossed galvanized steel cabinets standard. Cabinet feature furnace connectors.
- Upflow, horizontal right, and horizontal left without field modification. Downflow application require field kit, sold separately.
- Fully insulated foil-faced insulation.
- Split access doors in front of cabinet for easy service access.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available
- Painted cabinets
- High-temperature plastic drain pan

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION			
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
DE24A*	24,000	14	21	21-1/2	19	38	41	46	20
DE24B*						41	44	50	
DE24C*						45	51	55	
DE24D*						49	55	61	
DE24E*						54	59	62	
DE30A*	30,000	14	21	21-1/2	19	41	44	50	16
DE30B*						45	51	55	
DE30C*						49	55	61	
DE30D*						54	59	62	
DE30E*						58	64	66	
DE36A*	36,000	14 for 2, 3R; 17 for 4R	21	21-1/2	23	45	51	55	12
DE36B*						49	55	61	
DE36C*						54	59	62	
DE36D*						58	64	66	
DE36E*						59	68	76	
DE42A*	42,000	17	24-1/2	21-1/2	23	49	55	61	12
DE42B*						54	59	62	
DE42C*						58	64	66	
DE42D*						69	68	76	
DE42E*						63	75	80	
DE48A*	48,000	17	24-1/2	21-1/2	27	54	59	62	12
DE48B*						58	64	66	
DE48C*						59	68	76	
DE48D*						63	75	80	
DE48E*						69	82	90	
DE60A*	60,000	21	24-1/2	21-1/2	30	59	68	76	12
DE60B*						63	75	80	
DE60C*						66	78	85	
DE60D*						69	82	90	

Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications. 2) Metal drain pan 3) For all coils – Liquid line 3/8 ODS; suction line 3/4" ODS for DC24-36, 7/8"

DE Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

ASK FOR ASPEN

DE Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.